

Variational Calculations for Liquid Na-Cs Alloy

II. The Heat Capacity at Constant Pressure

Nikolay Dubinin^{1,2}

¹⁾ Ural Federal University, Mira st. 19, 620002 Ekaterinburg, Russia

²⁾ Institute of Metallurgy of the Ural Branch of the Russian Academy of Sciences,
 Amundsen st. 101, 620016 Ekaterinburg, Russia

Copyright © 2014 Nikolay Dubinin. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Abstract

The heat capacity at constant pressure of the Na-Cs equiatomic liquid alloy at $T=373\text{K}$ is calculated by the variational method with hard-sphere reference system. It is found that the Krasco-Gurskiy model pseudopotential with the Geldart-Vosko exchange-correlation function gives a slightly better agreement with the experiment than the local Animalu-Heine model pseudopotential with the Toigo-Woodruff exchange-correlation function.

Keywords: Variational method, pseudopotential theory, liquid binary metal alloy, heat capacity at constant pressure

The heat capacity at constant pressure, c_p , is determined as follows:

$$c_p = T \left(\partial \Omega / \partial T \right)_P, \quad (1)$$

where Ω is the mean atomic volume, P – pressure, T – temperature.

In present study, Eq. (1) is calculated numerically from Ω obtained by the variational method (described in paper I [1]) by using the following condition:

$$\left(\partial F / \partial \Omega \right)_{T, \sigma_{ij}} = 0, \quad (2)$$

where F is the Helmholtz free energy, σ_{ij} – partial hard-sphere diameter, $i, j=1, 2$.

Two combinations of the pseudopotential model with the exchange-correlation function (ECF) are used: 1) the local Animalu-Heine (AH) [2] model pseudopotential (MP) with the Toigo-Woodruff (TW) [3] ECF; 2) the Krasco-Gurskiy (KG) [4] MP with the Geldart-Vosko (GV) [5] ECF. The local AH pseudopotential form-factor was presented in paper I. An analogous function

for the KG MP is written as follows:

$$\omega_i^{\text{KG}}(q) = -\left(4\pi z / \Omega q^2\right) \left\{ (2a_i - 1) q^2 r_{ci}^2 - 1 \right\} / \left(1 + q^2 r_{ci}^2\right)^2, \quad (3)$$

where z is the mean alloy valence, a_i and r_{ci} – i -th component parameters taken the same as for the corresponding pure metal.

Table 1. Values of pseudopotential parameters [3] used as input data

	A (a.u.)	R_M (a.u.)	a (a.u.)	r_c (a.u.)
Na	-0.1958	2.1148	0.4898	3.242
Cs	-0.1838	3.8677	0.8440	2.586

Table 2. Calculated heat capacity at constant pressure of the Na-Cs equiatomic liquid alloy at $T=373\text{K}$ in comparison with the experiment [6]

	AH-TW	KG-GV	Exp.
c_p / k_B	4.30	4.21	3.90

As it can be seen, the difference with experiment not more than 10 percent in both calculations, but the KG-GV combination gives a slightly better agreement.

References

- [1] N.E. Dubinin, Variational calculations for liquid Na-Cs alloy I. The isothermal compressibility, *Adv. Studies Theor. Phys.*, 8 (2014), paper I.
- [2] V.G. Vaks, A.V. Trefilov, *Fiz. Tverd. Tela* (Russia), 19 (1977), 244-258.
- [3] F. Toigo, T.O. Woodruff, Calculation of the dielectric function for a degenerate electron gas with interactions. I. Static limit, *Phys. Rev. B*, 2 (1970), 3958-3966.
- [4] G.L. Krasco, Z.A. Gurskiy, *Pithma v GETF* (Russia), 9 (1969), 596-601.
- [5] D.J.W. Geldart, S.H. Vosko, The screening function of interacting electron gas, *Can. J. Phys.*, 44 (1966), 2137-2171.
- [6] E.E. Shpilrain, D.N. Kagan, G.A. Krechetova, *Thermophysical Properties*, N 4 (Russia), IVTAN, 1978.

Received: February 24, 2014